

## \_\_\_\_ELECTRIC

## **DOSTEC AC**

## ADVANCED CONTROL DOSING PUMP

Diaphragm dosing pumps with advanced dosing control for an accurate and efficient automatic regulation.

DOSmart AC are characterized by high precision, wide possibility of regulation and high suction capacity even with viscous products.

There is an APP available for DOSmart AC pumps which allows to monitor and control easily the unit remotely. The APP also has the option to receive alarm messages through SMS and email.

#### **APPLICATIONS:**

- Water treatment
- Industrial processes
- Chemical industry
- Pulp & paper
- Agriculture

#### **OPERATING MODES**

- Analogue control (0/4-20mA)
- Proportional pulse control
- Batch dosing control
- Manual Flow Control

## ADVANCED DOSING FEATURES

- Remote activation (on/off)
- Test function
- Flow calibration
- Low Pulsation discharge function for a continuous flow (LP)
- Slow Suction function for high viscosity products (SS)
- ▼ Turndown ratio 1:3000
- High suction capacity
- Invariable flow, no pressure influence

## ADDITIONAL SAFETY DEVICES

- Level sensor
- Diaphragm leakage detector
- Pressure sensor
- Flow failure detector
- Temperature sensor



## ADVANCED DOSING FUNCTIONS

#### (ST) STANDARD



100% Operation

50% Operation

### (SS1) SLOW SUCTION



Slow suction cycle for a reliable dosing for high viscosity fluids

#### (SS2) SLOW SUCTION AND DISCHARGE







## **TECHNICAL FEATURES**

55-STA / 55-STD		MODELS				
		DOSMART 1.5	DOSMART 4	DOSMART 8	DOSMART 13	DOSMART 25
FLOW	l/h	1.5	4	8	13	25
	gph	0.40	1.05	2.10	3.40	6.60
PRESSURE MAX.	Bar	16	12	8	7	5
	psi	232	174	116	100	72
TURNDOWN RATIO		1:3000	1:3000	1:3000	1:3000	1:3000
STROKE	mm	2	2	2	4.5	4.5
STROKES/MIN.		50	95	150	91	162

# INPUTS / OUTPUTS AND COMMUNICATIONS

- Analogue input 0/4-20mA
- External pulse input
- Remote on/off input
- Level sensor input (pre-empty)
- Level sensor input (empty)
- Leakage detector input
- Pressure sensor input
- Serial port RS-485 ModBus
- 4-20mA output for registering and monitoring
- Pulse output for registering, monitoring and 2nd pump control
- Alarm output (relay)
- Level alarm output (relay)







# Advanced Control Dosing Pumps

- **❷** High Chemical Resistance
- Smart And Highly Efficient Dosing
- Turndown Ratio 1:3000
- O Dosing Flow From 1.5 to 60 L/H





Management System ISO 9001:2008





Helix Hydro Pty. Ltd. 23 Sir Laurence Drive Seaford, Victoria 3198 Phone: 03 9580 2122

Contact: enquiries@helixhydro.com.au Website: www.helixhydro.com.au VIC/TAS P: 0427 033 967
WA/NT P: 0409 115 895
NSW/ACT P: 0414 675 663
QLD P: 0417 733 508
SA P: 0427 033 967

